High-volume, high-quality scanning performance for document-intensive applications.

DR-G1130 DR-G1100 High-speed production scanners

you can







imageFORMULA DR-G1130 and DR-G1100 production scanners

These ultra-reliable, high-speed A3 production scanners quickly capture high volumes of documents in specialised applications where image quality and process efficiency are critical.

With a robust document feeder system and operator-friendly design, the DR-G1130 and DR-G1100 are ideal for handling large volumes of different document types, such as in centralised digital mailrooms or specialist scanning bureaus.

		8		
	B&W SPEED	COLOUR SPEED	DAILY DUTY CYCLE	AUTOMATIC DOCUMENT FEEDER
DR-G1130	130ppm	130ppm	30,000 scan/day	500 sheets
DR-G1100	100ppm	100ppm	25,000 scan/day	500 sheets

A4 Landscape speed

Productivity-boosting scanning

Give your productivity a boost with high-speed scanning up to 260 images per minute (A4 landscape) and benefit from a large 500-sheet document feeder, which saves valuable time for users who need to efficiently digitise hard copy files. Thanks to a dedicated chip, there's no loss of speed even when multiple image processing features are selected – producing more quality scans in less time.

Operator-friendly design

Designed with the user in mind, the new devices feature a front feed/u-turn paper path for a convenient operation. Combined with the positioning of the control panel, its ergonomic design allows users to load, feed and remove documents from a comfortably seated position – maximising job productivity and minimising worker fatique.

User-friendly Control Panel

An intuitive control panel, with clear message display screen and keys to launch pre-defined scan jobs has been incorporated to make it easy and simple to use. Save up to 99 pre-registered scan jobs using the Job Registration Tool.

Superior image quality results everytime

Both the DR-G1130 and DR-G1100 come with an array of intelligent image processing features, including advanced deskew to straighten documents that are fed in at an angle, MultiStream to create dual image outputs for OCR applications and Character Emphasis to improve legibility for better OCR recognition.



User-friendly control panel

Reliable handling of different document types

The DR-G1130 and DR-G1100 are designed to increase scanning reliability and minimise interruptions, for the best results every time.

Users can reliably process a wider range of document types thanks to a flat paper feeding path and three separation modes for scanning from ultra-thin paper (20gsm) to thick card stock (255gsm). Using the folio mode feature users can even scan A1-sized documents.

Sizes up to A3/11" x 17" Business cards

Canon scanners are built for quick error correction and minimum workflow disruption. In the rare event of a double feed an ultrasonic sensor immediately notifies the user for immediate resolution.



For enhanced reliability, staple detection sensors are also incorporated to help prevent any damage to documents, while a continuous manual feeding mode allows convenient controlled feeding to users when handling difficult documents. Lockable paper side guides also ensure smooth, productive scanning.

The document feeder has three selectable feeding modes (100, 300 and 500 sheets) that are adjustable according to the volume of the batches being scanned, saving time and increasing overall throughput.







Highest position (100 sheets) Middle position (300 sheets) Lowest position (500 sheets)

Great software for increased efficiency

CapturePerfect

Scan batches of documents quickly and easily with this intuitive application that offers multi-window and thumbnail views. It has flexible 'scanning to' options like scan to folder, email and SharePoint. A CapturePerfect Software Developer Kit (SDK) is also available.

Kofax VRS

Achieve excellent image quality results every time with Kofax VRS software. It makes scanning simpler and easier thanks to automatic image processing and document handling. Its industry-leading imaging quality improves readability and raises OCR rates so fewer re-scans are required.

Handle exceptions with optional flatbed

Scan bound books, journals and fragile media by adding the Flatbed Scanner Unit 101 for documents up to A4 or Flatbed Scanner Unit 201 for A3 scanning. Connected by USB, these flatbed scanners work seamlessly with the DR-G1130 and DR-G1100 in a smooth dual-scanning operation that lets you apply the same image-enhancement features to any scan.





A4 Flatbed Scanner Unit 101

Specifications for DR-G1100/DR-G1130 High Speed Production Scanners

Type Document Reading Sensor Optical Resolution Light Source Reading Side Interface Dimensions Weight Power Requirements Power Consumption Operating Environment Environmental Compliance	A3 Desktop Type Sheet Fed Scanner CMOS CIS 3 Line Sensor 600dpi RGB LED Front / Back / Duplex High Speed USB 2.0 Tray Closed: 480 (W) x 535 (D) x 315 (H)mm Tray Opened: 480 (W) x 723 (D) x 390 (H)mm 22.8kg AC220 - 240V (50/60Hz) Scanning: 94.3W or less, Sleep mode: 1.7W or less, Power turned off: 0.3W or less 10 - 32.5°C (50 - 90.5°F), Humidity: 20 - 80% RH ROHS and ENERGY STAR		
READING SPEED*		DR-G1100	DR-G1130
(A4, Portrait) B&W / Greyscale Colour	200dpi / 300dpi 200dpi 300dpi	75ppm / 150ipm 75ppm / 150ipm 75ppm / 150ipm	100ppm / 200ipm 100ppm / 200ipm 100ppm / 170ipm
(A4, Landscape) B&W / Greyscale Colour	200dpi / 300dpi 200dpi 300dpi	100ppm / 200ipm 100ppm / 200ipm 100ppm / 170ipm	130ppm / 260ipm 130ppm / 200ipm 130ppm / 170ipm
DOCUMENT SPECIFICATIONS Width Length Thickness Long Document Mode Paper Separation Feeder Capacity	50.8 - 305mm 70 - 432mm Continuous Feeding: 20 - 209g/m², 0.04 - 0.25mm Non-Separation Mode: 20 - 255g/m², 0.04 - 0.03mm 3000mm max. Retard Roller and Pre-separation method 500 sheets (selectable: 500, 300, 100)		
OUTPUT Resolution Mode	150 x 150dpi, 200 x 200dpi, 240 x 240dpi, 300 x 300dpi, 400 x 400dpi, 600 x 600dpi Black and White, Error Diffusion, Advanced Text Enhancement, Advanced Text Enhancement II, 256-level Grayscale, 24-bit Color		

SPECIAL FEATURES	Automatic Page Size Detection, Deskew, 3-dimensional Colour Correction (partly by Driver), Colour Dropout (RGB), Image Rotation, MultiStream, Preset Gamma Curve, Contrast Adjustment, Prescan, Staple Detection, Skip Blank Page, Select Scanning Document Side, Punch Hole Removal, Moire Removal, Folio Mode, Scan Area Setting Text Orientation Recognition, Background Smoothing, Rapid Recovery Scan, Double Feed Detection (Length By Firmware)
BUNDLED SOFTWARE For Windows OS	ISIS /TWAIN Driver (Windows XP / VISTA / 7 / 8) CapturePerfect Kofax VRS (CapturePerfect SDK available through Canon Business Solutions Developer Programme – www.canon-europe.com/bsdp)
Options	Post Imprinter Barcode Module Patchcode Decoder Flatbed Scanner Unit 101 Flatbed Scanner Unit 201
Consumables Suggested Daily Duty Cycle	Exchange Roller Kit Separation Pad Ink Cartridges (Red, Blue, Green) DR-G1130: 30,000 sheets/day DR-G1100: 25,000 sheets/day

^{*}Scanning speeds depends on the specification of PC and the settings of function.

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and ⊚ all company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their market and/or countries.

Specifications for imageFORMULA Flatbed Unit 101 and Flatbed Unit 201

	Flatbed Scanner Unit 101	Flatbed Scanner Unit 201	
Type	Universal A4 Flatbed Option	Universal A3 Flatbed Option	
Document Reading Sensor	· CCD !	Sensor	
Optical Resolution	1200dpi	600dpi	
Light Source	LED	(RGB)	
Interface	High speed USB 2.0		
Dimensions	290 (W) x 512 (D) x 88.5 (H)mm	571 (W) x 436 (D) x 96 (H)mm	
Weight	3.5kg (without AC adaptor)	8.5kg (without AC adaptor)	
Power Requirements	AC220 - 240V (50/60Hz)	AC100 - 240V (50/60Hz)	
Power Consumption	Scanning: <15.2W, Sleep Mode: <5.1W,	Scanning: <21W, Sleep Mode: <3.1W,	
	Power off: <0.5W	Power off: <0.3W	
Environmental Compliance	RoHS and ENERGY STAR		
READING SPEED*			
B&W / Greyscale (200/300dpi)	3 Seconds	3.5 Seconds (A3)	
Colour (200dpi)	3 Seconds	4.5 Seconds (A3)	
Colour (300dpi)	4 Seconds	4.5 Seconds (A3)	
DOCUMENT SPECIFICATION			
Width	up to 215.9mm	up to 297.4mm	
Length	up to 355.6mm	up to 421.8mm	
		.,	
OUTPUT	400 400 1 450 450 1 000 000 1 010 010 1 700 700 1	400 4001 450 4501 000 0001 010 0101 700 7001	
Resolution	100 x 100dpi, 150 x 150dpi, 200 x 200dpi, 240 x 240dpi, 300 x 300dpi,	100 x 100dpi, 150 x 150dpi, 200 x 200dpi, 240 x 240dpi, 300 x 300dpi,	
	400 x 400dpi, 600 x 600dpi, 1200 x 1200dpi	400 x 400dpi, 600 x 600dpi	
Mode	Black and White, Error Diffusion, Advanced Text Enhancement II,		
	bit Colour, Auto Colour Detection		
SPECIAL FEATURES	Automatic Page Size Detection, Deskew, Ambient Light Cancelling Mode, Scan Area Setting.		
	Additional features inho	erited from DR-Scanners	

^{*}Scanning speeds depend on the specification of PC and the settings of function.

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and ⊚: all company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their market and/or countries.











Canon UKItd canon.co.uk/scanners

Canon Europe canon-europe.com

English Edition © Canon Europa N.V., 2013 Canon Europe Ltd 3 The Square Stockley Park Uxbridge Middlesex UB11 1ET

United Kingdom

